



# Millennium Series 2001 Floating Wood Flooring Adhesive

MILLENNIUM SERIES

**DESCRIPTION:**

Millennium Series 2001 Floating Wood Floor Glue is formulated to install all wood floating floors. It is flexible enough to give and bend with the normal movement of floating floors without breaking the bond. 2001 provides an aggressive water resistant bond to the wood.

**INSTALLING THE FLOOR:**

Always follow the wood manufacturers' recommendations for sub-floor moisture, sub-floor levelness, expansion space and acclimation requirements. All sub-floors must be smooth within 3/16" in 6' and structurally sound, clean, dry, smooth, and free of dust, wax, oils, paint, curing agents and any other contaminants that would interfere with a good bond.

**RECOMMENDED SUBSTRATES:**

- Concrete
- Portland Based Underlayments
- Properly Prepared Gypsum
- APA Approved Plywood
- Terrazzo
- Fiber Cement Underlayment
- Radiant Heated Subfloors
- Properly Prepared VCT (Single Layer)
- Properly Prepared Sheet Vinyl (Single Layer, fully adhered)

**CLEAN-UP:**

Remove the adhesive from the wood floor surface as soon as possible before the adhesive dries. Use a soft cloth and Mineral Spirits carefully to not harm the finish. Clean equipment and tools with Mineral Spirits while the adhesive is still wet.

**CAUTION:** Mineral Spirits are flammable. Read and follow all precautions on container label

**RESTRICTIONS:**

1. For Interior installations only.
2. Do not install over adhesive residue including cutback.
3. Do not install when ambient temperature is not between 60°F & 95°F.
4. Do not install when ambient relative humidity is above 65%.
5. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the user's intended use.

**PACKAGING:**

- 16 oz bottle

**COVERAGE:** 365 LINEAR FEET PER BOTTLE

**WARRANTY:**

Royal Adhesives and Sealants offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800 763-7272 or visiting [www.parabond.com](http://www.parabond.com)

Technical Data	
Base Polymer	Vinyl Acetate
Color	Yellow
Solids	45-50%
VOC Content	<1 grams / Liter
pH	5
Consistency	Yellow Liquid
Shelf Life	One Year in Unopened Container
Storage	40°-95°F
Application Temperature	65°-95°F (18°-35°C)
Traffic Restrictions	Foot Traffic after 8 hours, Heavy Traffic 24 hours
Open Time	Up to 45 Minutes
Freeze Thaw Stability	Store Above 40°F

863 SE Main Street • Simpsonville, SC 29681

Phone: 1-800-763-7272 • ISO 9001 Certified

[www.parabond.com](http://www.parabond.com)

4/1/2014