



Signature Series 5060

Pressure Sensitive Adhesive

Signature Series

DESCRIPTION:

Signature Series 5060 Pressure Sensitive Adhesives is an Acrylic Emulsion designed for use with multiple types of floor coverings. 5060 is approved for the installation of dimensionally stable vinyl-backed carpet tiles, vinyl tile & plank, fiberglass backed sheet vinyl & approved cushions in double glue down applications. Due to its pressure sensitive characteristics, 5060 eliminates concern about installing a non-porous backed floor covering over a non-porous substrate.

Signature Series 5060 qualifies for Floor Score Certification and the Carpet & Rug Institutes Green Label Plus Program. This is a third party certification with the most stringent VOC regulations in the country.

SUBFLOOR PREPARATION:

Follow all manufacturer's recommendations and industry standards regarding subfloor preparation. Moisture tests are required on all concrete subfloors regardless of grade level if freshly poured or classified as an older slab. Moisture testing should be performed by ASTM F1869 Calcium Chloride Tests with moisture levels not to exceed five (5) pounds per one thousand (1000) square feet per Twenty-Four (24) hours or ASTM F2170 In Situ Relative Humidity Test with moisture levels not to exceed eighty (80) percent. Additional information with regard to these tests and results can be obtained through Royal Adhesives & Sealants Technical Service Department.

INSTALLATION DIRECTIONS:

1. Refer to all manufacturer's recommendations prior to installation to determine suitability of all materials to be used, approved substrates, subfloor preparation, etc.
2. Sub-floor must be clean, dry, smooth and free of any contamination, which may interfere with the adhesive bond.
3. Where sub-floor is extremely porous, adhesive absorption may be in question, therefore it is recommended that the subfloor be primed with Parabond® M-620 Primer.
4. Refer to all floor-covering manufacturers' recommendations regarding layout, cutting, seaming and maintenance.
5. Spread adhesive using the recommended trowel. Use the dry installation method in "tile over tile" applications and for situations requiring a releasable installation. (carpet tile, double stick). If carpet tiles are installed "wet", a permanent bond may result.
6. Roll floor covering as per manufacturers' recommendations.

7. Do not wet clean floor covering for a minimum of 14 days. This will allow the adhesive to properly cure.
8. Once adhesive turns clear, floor covering must be placed within 2-4 hours MAXIMUM.

RECOMMENDED SUBSTRATES:

- Concrete
- Portland Based Underlayments
- Properly Prepared Gypsum
- APA Approved Plywood
- Terrazzo
- Fiber Cement Underlayment
- Radiant Heated Subfloors
- Properly Prepared VCT (Single Layer)
- Properly Prepared Sheet Vinyl (Single Layer, fully adhered)

RESTRICTIONS:

1. Refer to flooring manufacturer for recommendation.
2. For interior installations only.
3. Do not install over adhesive residue including cutback.
4. Do not install when MVER is over 5 lbs per 1,000 sf per 24 hours, per ASTM F1869.
5. Do not install when relative humidity is over 80%, per ASTM F2170.
6. Do not install when ambient temperature is not between 60°F & 90°F.
7. Do not install when ambient relative humidity is above 65%.
8. The dimensional stability of some vinyl flooring products is very sensitive to fluctuations in ambient environment conditions. Royal Adhesives & Sealants is not responsible for installation issues caused by dimensional changes in flooring.
9. It is the sole responsibility of the installer to determine suitability and compatibility of the adhesive for the user's intended use.

CUSHION-BACKED VINYL: For a releasable installation apply the adhesive to the substrate using a 3/8" short nap roller in a full spread installation (250-350 sf/gal spread rate). Do not apply adhesive in a perimeter installation. Allow the adhesive to set dry with no transfer to the finger, tacky condition before installing sheet vinyl.



863 SE Main Street • Simpsonville, SC 29681
Phone: 1-800-763-7272 • ISO 9001 Certified

www.parabond.com

11/7/2017





Signature Series 5060 Pressure Sensitive Adhesive

Signature Series

PACKAGING:

- One 4-Gallon Pail
- Four x 1-Gallon Case

CLEAN-UP:

Remove wet adhesive immediately with a damp cloth. Use Mineral Spirits or M-315 Cleaner to remove dried adhesive. **CAUTION: Mineral Spirits are flammable. Read and follow all precautions on container label.**

WARRANTY:

Royal Adhesives and Sealants offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800 763-7272 or visiting www.parabond.com.

FLOORING	TROWEL	ESTIMATED SPREAD RATE
Vinyl Tile & Plank		160-180 sq/ft per gallon 18-20 sq/yards per gallon
Vinyl Backed Carpet Tile / Non PVC Carpet Tile		125-150 square feet per gal 14-17 sq/yards per gallon
Cushion-Backed or Fiber glassed-Backed vinyl sheet flooring		250-350 square feet per gal 27-38 sq/yards per gallon



863 SE Main Street • Simpsonville, SC 29681
Phone: 1-800-763-7272 • ISO 9001 Certified

www.parabond.com

11/7/2017





Signature Series 5060 Pressure Sensitive Adhesive

Signature Series

Technical Data	
Base Polymer	Acrylic
Color	White
Solids	50%-52%
VOC Content	<1 gram per liter
pH	7
Consistency	Fluid Paste
Trowelability	Light, Easy
Shelf Life	Two Year in Unopened Container
Storage	40°-95°F
Application Temperature	65°-95°F (18°-35°C)
Traffic Restrictions	Foot Traffic immediately after rolling, Heavy traffic 12 Hours
Open Time	Up to 4 hours depending on ambient conditions
Drying Time	45-60 minutes depending on ambient conditions
Freeze Thaw Stability	5 cycles @ 20°F



863 SE Main Street • Simpsonville, SC 29681
Phone: 1-800-763-7272 • ISO 9001 Certified

www.parabond.com

11/7/2017

